

Inserts for Busch-Dimmer® units
Busch-rotary dimmer
Flush-mounted, LED, 2-100 W



With rotary control, two-way switch and soft-catch.

2-wire connection (neutral conductor not required)

Optimised for dimming of retrofit LED lamps (LEDi).

For dimmable Retrofit-LEDs (LEDi).

For dimmable Retrofit-LEDs (LEDi) with conventional or electronic transformers.

For incandescent lamps, 230 V tungsten halogen lamps, low-voltage halogen lamps with conventional or electronic transformers and dimmable energy-saving halogen lamps.

Mix operation of LEDi with conventional loads possible.

Via mode switch adjustable between leading edge control and trailing edge control.

Low-noise level by MOSFET transistors.

With electronic short-circuit protection.

With electronic overload protection.

With adjustable minimum brightness.

Without cover plate.

Rated voltage: 230 V~, + 10% / - 10%

Rated frequency: 50 Hz/60 Hz

Nominal power: 2 - 100 W/VA (retrofit LED loads).

Nominal power: 10 - 250 W/VA (non-LED loads).

Protection class (Device): IP 20, Temperature range (Device): 0 °C to 35 °C,

Illuminable with neon lamp. Neon lamp included in delivery with cover plate., In the case of conventional transformers, take ~20% transformer loss into account., In case of electronic transformers, 5 % transformer losses., Also applicable for 1gang 2way installations., Provided with terminal for net disconnection devices., Only in conjunction with standard flush-mounting boxes according to DIN 49073, Part 1, erect or Busch-Jaeger No. 3040 wallbox stonework, 3050 wallbox cavity wall or 3060 wallbox concrete)

Order Code : 2CKA006512A0335

Article No. : 6523 U-102-500

EAN: 4011395212684

